

WL350 Firewall®

Excellent purifying performance,
easy operation and stylish design



Purified water for the workplace

With a choice of hot and cold water, the WL350 Firewall is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL350 features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T and to NSF/ANSI-53 for the reduction of lead, asbestos, and cysts, meaning they offer the best possible filtration.



Firewall purification

Waterlogic's patented Firewall technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



BioCote® protection

The key surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

Certified purity for peace of mind

The Firewall technology has been tested and certified by the IAPMO R&T to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – no other water cooler features these standards of certification for microbiological water treatment systems together. This means that Firewall technology delivers the safest water possible for the workplace.

*BioCote® technology does not protect users or others against disease causing bacteria, germs, viruses or other harmful organisms. This technology is not a substitute for good hygiene and/or cleaning practices. BioCote® has not been tested or proven effective against SARS-CoV-2.

Features

Firewall UV technology purifies the water at the point of dispense and sanitizes the faucet with every use

Energy saving sleep mode to significantly reduce power consumption when unit is not in use

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Water options



Number of users

 up to 30



Call us today

Blue Mountain Pure, LLC

Tel: 877-474-7332

www.bluemountainpure.com

info@bluemountainpure.com

For more information, visit

www.bluemountainpure.com

A KnightHorst Managed Company.

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

13.6"/345mm (W) x 40.2"/1022mm (H) x 14.4"/367mm (D)

Countertop:

13.6"/345mm (W) x 17.7"/450.5mm (H) x 14.4"/367mm (D)

Dispensing area height

8.5" (215mm)

Weight

Countertop: 42lbs (19kg)

Freestanding: 58lbs (26kg)

Standard filtration supplied

Freestanding: Carbon Block (CBC) with lead, cyst and asbestos reduction, Granular Activated Carbon (GAC)

Countertop: Carbon Block (CBC) with lead, cyst and asbestos reduction

Storage capacity

Hot tank: 1.6 liters

Cold tank (Freestanding): 4 liters

Cold tank (Countertop): 2 liters

Compressor

Compressor 120V/60Hz

Water temperatures settings

Cold: 41°F/ 5°C

Hot: 187°F/ 85°C



Tested and certified

Firewall technology is certified by NSF/ANSI 61 to NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 272 and CSA B482.1.



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

USCP208B-17/06/20